



Indoor Lighting

LED Panel light, square

- The luminaire is suitable for computer workplaces
- Standard dimensions for easy integration into existing infrastructure
- Additional mounting situations realizable by separately available installation packages:
surface-mounted and suspended luminaire
- Suitable for: offices, schools, hotels, restaurants, conference rooms and hallways

ELECTRONICS	
Luminaire type	Panel light
Driver	external
Protection class	Class I
Power consumption*	34 W
Rated voltage	220 – 240 V/AC
Power factor	≥ 0.95 c
Dimming (optional)	1 – 10 V / DALI
Operating temperature Ta	-20°C to +45°C
LIGHT TECHNOLOGIES	
System luminous flux	3,400 lm (4,000 K)
Luminous flux over lifetime	70% after 50,000 operating hours
Color temperature	4,000 K
Color rendering index	≥ 80
Optics	opaque or prism lenses

ADDITIONAL DATA		
Materials	Aluminum housing, white	
IP certification (Luminaire)	IP 40	
Certification		
Efficiency class		
GRID CEILINGS		
Luminaire dimensions (L x W x H):	Weight:	Ceiling dimensions:
595 x 595 x 10 mm	3.9 kg	600 x 600 mm
620 x 620 x 10 mm	3.9 kg	625 x 625 mm

* All performance parameters are based on an ambient temperature of 25°C