

Luminare	Luminous flux	Efficacy luminare [lm/W]		Rated power [W]		operating current LED [mA]	
		3.000K	4.000K	3.000K	4.000K	3.000K	4.000K
Helius 120	1.000	130	137	7,7	7,3	138	133
	1.250	132	139	9,5	9,0	174	165
	1.500	133	140	11,3	10,7	214	200
	1.750	134	141	13,1	12,4	250	237
	2.000	133	141	15,0	14,2	289	274
	2.250	132	140	17,0	16,1	330	313
	2.500	131	138	19,1	18,1	370	351
	2.750	129	136	21,3	20,2	407	386
	3.000	128	134	23,5	22,4	458	427
	3.250	126	133	25,8	24,5	501	477
Helius 120/121	3.500	124	131	28,2	26,8	553	520
	3.750	123	129	30,5	29,0	596	568
	4.000	121	127	33,0	31,4	644	613
	4.250	136	143	31,2	29,8	316	302
	4.500	135	142	33,3	31,7	337	321
	4.750	134	141	35,4	33,7	362	345
	5.000	133	140	37,6	35,7	384	365
	5.250	132	140	39,7	37,6	410	388
	5.500	131	139	42,0	39,7	433	409
	5.750	130	138	44,2	41,8	456	431
	6.000	129	136	46,4	44,0	483	453
	6.250	128	135	48,8	46,2	508	481
	6.500	126	134	51,5	48,5	535	504
	6.750	125	132	54,0	51,0	561	530
	7.000	123	131	57,0	53,5	592	556
	7.250	121	129	60,0	56,0	623	581
	7.500	119	128	63,0	58,5	654	607
7.750	117	127	66,0	61,0	685	633	
8.000	116	125	69,0	64,0	716	663	
Helius 121	8.250	132	140	62,5	59,0	430	406
	8.500	131	139	65,0	61,0	452	420
	8.750	130	139	67,5	63,0	470	438
	9.000	129	137	70,0	65,5	487	455
	9.250	127	136	73,0	68,0	508	473
	9.500	126	135	75,5	70,5	525	490
	9.750	125	134	78,0	73,0	542	507
	10.000	123	132	81,0	75,5	563	524
	10.250	123	131	83,5	78,0	580	541
	10.500	122	130	86,0	80,5	603	559
	10.750	121	130	89,0	83,0	624	576
	11.000	120	129	92,0	85,5	645	599
	11.250	118	128	95,0	88,0	666	617
	11.500	117	126	98,5	91,0	691	637
11.750	-	125	-	94,0	0	657	
12.000	-	124	-	97,0	0	677	

Simmons signs Limited reserves the right to alter or improve this guide without prior notice.